FIX-N-FAX #177

CALIFORNIA DEPARTMENT OF FORESTRY AND FIRE PROTECTION

Number 177 Mandatory Compliance

Date: May 2000

Waterous CPK-3, 475 GPM (Modified)

The following information is provided by the Fleet Management staff in the Coastal Cascade Region. The early production hydrostatic pumping systems were put in service equipped with a Waterous CPK-3, 475 gpm, fire pump with wet packing.

In 1996, CDF modified and tested this pump with a mechanical seal. The parts needed to convert to a mechanical seal are the same used in the later CPK-3, 500 gpm pumps, EXCEPT THE IMPELLER DRIVE SHAFT. New shafts have been manufactured and are available from the Davis Equipment Facility.

NOTE: These pumps disassemble and assemble per the instructions for the later CPK-3, 500 gpm units. Pump gear cases are the same; mechanical seals are the same; retainers are the same; along with both ends of the 475 gpm (modified), and utilize the same components as the later 500 gpm pumps.

Parts to modify: (Waterous)

(1)	Spacer Impellers	51039
(2)	Interstage Seal	61178
(3)	Gasket (heads)	50714
(4)	Valve Flapper	61180
(5)	Impeller Driveshaft	CDF manufactured

Mobile Equipment Inventory Listing of Affected Fire Engine

<u>X NO.</u>	<u>LICENSE</u>	<u>YR</u>	MAKE	<u>PILOT</u>	<u>PUMP</u>	REGION/UNIT
	852113	78	INTL	12	Waterous CPK-3 475 Pack	9 - Historical
04X256	874639	83	INTL	5	Waterous CPK-3 475 Pack	2 - Tehama-Glenn
04X002	409051	85	INTL	14	Waterous CPK-3 475 Pack	2 - Butte
05X194	382353	86	INTL	1	Waterous CPK-3 475 Pack	2 - Mendocino
04X094	413546	87	INTL	5	Waterous CPK-3 475 Pack	3 - San Bernardino
04X257	413549	87	INTL	5	Waterous CPK-3 475 Pack	9 - Fire Academy
04X009	382337	88	INTL	5	Waterous CPK-3 475 Pack	2 - Siskiyou
04X021	382346	88	INTL	5	Waterous CPK-3 475 Pack	2 - Siskiyou
04X030	382348	88	INTL	5	Waterous CPK-3 475 Pack	2 - Tehama-Glenn
04X040	382345	88	INTL	5	Waterous CPK-3 475 Pack	2 - Butte
04X043	382347	88	INTL	5	Waterous CPK-3 475 Pack	2 - Butte
05X218	382388	88	INTL	1	Waterous CPK-3 475 Pack	2 - Nevada-Yuba- Placer

(see FIX-N-FAX INDEX)